



SCM 20 ASL PRO : 2 - w a y a c t i v e

- Features
- 25mm soft dome HF unit.
 - Full "SL" spec ATC bass driver with integral 75mm soft dome.
 - 9kg precision machined and optimised motor assembly.
 - LF contour control
 - On board ATC built two way 300W amplifier
 - Heavily damped Aluminium cabinet
 - 6 year warranty

Specifications

Drivers : HF 25mm, Mid/LF 75/150mm **Amplitude Linearity ($\pm 2\text{dB}$):** 80Hz-17kHz **Cut-off Frequencies (-6dB , free-standing) :** 60Hz, 22kHz
Horizontal Dispersion : $\pm 80^\circ$, Coherent **Vertical Dispersion :** $\pm 10^\circ$, Coherent **Max. Continuous SPL (1 metre) :** 108dB **Crossover Frequency :** 2.8kHz
Input Connectors : Male XLR **Input Sensitivity :** 1V **Input Sensitivity Trim :** $\pm 6\text{dB}$ **Input Impedance :** Balanced $> 10\text{k}\Omega$
Amplifier Output : Bass 250W, High 50W **Filters :** Even Order Critically Damped
Overload Protection : Active FET momentary gain reduction plus thermal tweeter protection **Front Panel Indicators :** Power On indicator, Gain Reduction warning
LF EQ : $+6\text{dB}$ @ 40Hz **Dimensions (HxWxD) :** 448 x 270 x 310mm (17.6" x 10.6" x 12.2") **Weight :** 30kg / 66lbs

ATC reserves the right to vary products and specifications without prior notice.

